

Counting system KERN CCA

NEW



High-resolution counting system with EC type approval [M] to count the smallest parts in the largest quantities, counting resolution up to 300.000.000 points

Features

- The highly accurate KERN CCS counting system can replace a whole range of individual balances, efficiently and at a reasonable price
- Thanks to EC type approval [M], it is also suitable for use in verified applications
- The balances are connected to one another with an RS-232 Y-cable (KERN CCA-A01, included with delivery), which also allows you to connect a printer

Reference scale KERN EWJ

- This precision balance, which can be used as an individual balance, also fulfills the highest demands through connection with a high-capacity weighing bridge
- Easy to use:** All primary functions have their own key on the keypad
- Automatic internal adjustment,** time-controlled every 2 h, guarantees high degree of accuracy and makes the balance independent of its location
- Draught shield standard, weighing space W×D×H 134×128×80 mm
- Protective working cover** included with delivery

Quantity scale KERN IFS

- The high-accuracy quantity counting takes place on the weighing platform (= weighing bridge) KERN CCA. In this way even the smallest of parts can be counted in large volumes
- Tough industry standard** suitable for use in harsh industrial applications
- Tough industry standard** suitable for use in harsh industrial applications
- Ergonomic display device** with large keypad and high-contrast LCD display for easy entry and reading of, e.g., tare weights, reference weights, limit values etc.
- Three displays** for weight display (verifiable), reference weight, total pieces
- 100 item memories** for master data such as reference weight, reference quantity, container weight (PRE-TARE) etc.
- Printout of date and time for GLP and GMP compliant data logging
- Precise counting:** The manual reference weight optimisation gradually improves the average value of the piece weight
- Totalising** of pieces when counting
- Aluminium Single-Point load cell** (1×3000 e), protection against dust and water splashes IP65

STANDARD	CAL INT	CAL EXT	MEMORY	RS 232	USB	PCS	RECIPE	SUM	%	PERCENT	UNIT	TOL	A	B	DMS	2 DAYS	OPTION	DAkkS	FACTORY	
EWJ	IFS	IFS	occupied	EWJ							EWJ	IFS	IFS	EWJ			EWJ	ACCU +3 DAYS	IFS	M +3 DAYS

Model	Weighing capacity Quantity scale [Max] kg	Readability Quantity scale [d] g	Weighing plate	Weighing capacity Reference scale [Max] g	Readability Reference scale [d] g	Counting resolution Points	Smallest part weight [Normal] g/piece	Option Verification	
								M	KERN
CCA 6K-5M	3 6	1 2	A	600	0,01	6.000.000	0,2		965-228-216
CCA 10K-5M	6 15	2 5	A	600	0,01	15.000.000	0,2		965-228-216
CCA 30K-5M	15 30	5 10	B	600	0,01	30.000.000	0,2		965-228-216
CCA 60K-5M	30 60	10 20	B	600	0,01	60.000.000	0,2		965-229-216
CCA 100K-5M	60 150	20 50	C	600	0,01	150.000.000	0,2		965-229-216
CCA 300K-5M	150 300	50 100	C	600	0,01	300.000.000	0,2		965-229-216

Pictograms

Internal adjusting: Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)	KERN Communication Protocol (KCP): It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems	Protection against dust and water splashes IPxx: The type of protection is shown in the pictogram.
Adjusting program CAL: For quick setting up of the balance's accuracy. External adjusting weight required		
Easy Touch: Suitable for the connection, data transmission and control through PC, tablet or smartphone		
Memory: Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.	GLP/ISO log: The balance displays serial number, user ID, weight, date and time, regardless of a printer connection	Stainless steel: The balance is protected against corrosion
Alibi memory: Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.	GLP/ISO log: With weight, date and time. Only with KERN printers	Suspended weighing: Load support with hook on the underside of the balance
Data interface RS-232: To connect the balance to a printer, PC or network	Piece counting: Reference quantities selectable. Display can be switched from piece to weight	Battery operation: Ready for battery operation. The battery type is specified for each device
RS-485 data interface: To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible	Recipe level A: The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out	Rechargeable battery pack: Rechargeable set
USB data interface: To connect the balance to a printer, PC or other peripherals	Recipe level B: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display	Universal mains adapter: with universal input and optional input socket adapters for A) EU, CH, GB; B) EU, CH, GB, USA; C) EU, CH, GB, USA, AUS
Bluetooth* data interface: To transfer data from the balance to a printer, PC or other peripherals	Recipe level C: Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display, multiplier function, adjustment of recipe when dosages are exceeded or barcode recognition	Mains adapter: 230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available
WLAN data interface: To transfer data from the balance to a printer, PC or other peripherals	Totalising level A: The weights of similar items can be added together and the total can be printed out	Power supply: Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request
Control outputs (optocoupler, digital I/O): To connect relays, signal lamps, valves, etc.	Percentage determination: Determining the deviation in % from the target value (100 %)	Weighing principle: Strain gauges Electrical resistor on an elastic deforming body
Analogue interface: to connect a suitable peripheral device for analogue processing of the measurements	Weighing units: Can be switched to e.g. nonmetric units at the touch of a key. See balance model. Please refer to KERN's website for more details	Weighing principle: Tuning fork A resonating body is electromagnetically excited, causing it to oscillate
Interface for second balance: For direct connection of a second balance	Weighing with tolerance range: (Checkweighing) Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model	Weighing principle: Electromagnetic force compensation Coil inside a permanent magnet. For the most accurate weighings
Network interface: For connecting the scale to an Ethernet network	Hold function: (Animal weighing program) When the weighing conditions are unstable, a stable weight is calculated as an average value	Weighing principle: Single cell technology: Advanced version of the force compensation principle with the highest level of precision
Wireless data transfer: between the weighing unit and the evaluation unit using an integrated radio module		Verification possible: The time required for verification is specified in the pictogram
*The Bluetooth® word mark and logos are registered trademarks owned by Bluetooth SIG, Inc. and any use of such marks by KERN & SOHN GmbH is under license. Other trademarks and trade names are those of their respective owners.		DAkkS calibration possible: The time required for DAkkS calibration is shown in days in the pictogram
		Package shipment: The time required for internal shipping preparations is shown in days in the pictogram
		Pallet shipment: The time required for internal shipping preparations is shown in days in the pictogram

KERN – Precision is our business

To ensure the high precision of your balance KERN offers you the the appropriate test weight in the international OIML error limit classes E1-M3 from 1 mg - 2500 kg. In combination with a DAkkS calibration certificate the best pre-requisite for proper balance calibration.

The KERN DAkkS calibration laboratory today is one of the most modern and best-equipped DAkkS calibration laboratories for balances, test weights and force-measurement in Europe.

Thanks to the high level of automation, we can carry out DAkkS calibration of balances, test weights and force-measuring devices 24 hours a day, 7 days a week.

Range of services:

- DAkkS calibration of balances with a maximum load of up to 50 t
- DAkkS calibration of weights in the range of 1 mg - 2500 kg
- Volume determination and measuring of magnetic susceptibility (magnetic characteristics) for test weights
- Database supported management of checking equipment and reminder service
- Calibration of force-measuring devices
- DAkkS calibration certificates in the following languages DE, GB, FR, IT, ES, NL, PL
- Conformity evaluation and reverification of balances and test weights

Your KERN specialist dealer: